TOPGUN 515F 3 PHASE DC MIG WELDING MACHINE TGWMIG515F

Package Includes

Users Manual

10 MTR Interconnecting Leads

Seperate Wire Feeder

4MTR MB36 Euro-Fit Mig Torch

8 MTR Earth Lead with Topgun 600A Clamp

8 MTR Electrode Holder Lead Twist Lock

0.8mm - 0.9mm "V" Solid Rollers

1.2mm - 1.6mm "V" Solid Rollers

0.9mm - 1.2mm "F" Flux Cored Rollers

1.2mm - 1.6mm "F" Flux Cored Rollers

Welding Trolley with Storage Drawer

Quick Connect Fittings for Tig Torch and Gas Hose

Twin Gauge Regulator

MB 36 Consumable Kit

Gas Hose 2MTR with Quick Connect Fitting



pecifications	
put Voltage (V)	415 A/C
requency (Hz)	50/60 Hz
utput Current Range (A)	40 - 500A MIG
ated Duty Cycle (%)	60% @ 500A
	100% @ 400A
achine Weight	(Assembled) 121 Kg
achine Dimensions(mm)	(Assembled) 1040 x 1450 x 510
ackage weight	(Power Source) 30 Kg (SWF) 46 Kg (Storage Drawer) 15Kg (Welding Trolley) 30 Kg
ackage Dimensions (mm)	(Power Source) 760x320x580 (SWF) 820x460x560 (Storage Drawer) 770x260x370 (Welding Trolley) 1110x510x270
arranty	3 Years



60

© 0 6 ٥

S

In

0

R

N

N

W